

AMS UHD Automatic Barrier

Maximum 9m Boom Length

Bottom Skirt and Hi-Bar (Top & Bottom) Skirting available

100% Duty Cycle Product

Single Phase Supply, 3 Phase Motor

Programmable Control Panel c/w Diagnostic Screen Display



Technical Specification

| | |
|-----------------------------------|--|
| Maximum Boom Length | 9m Plain Pole, 8m with Bottom Skirt or 6.5m with Hi-Bar (Top and Bottom Skirt) |
| Boom Diameter | 100mm Round |
| Opening / Closing Duration | 4 to 9 seconds (adjustable – also varies depending on Barrier configuration) |
| Drive Unit | Inverter Driven 3 Phase Motor and Wormed Gearbox |
| Power Supply | 230VAC, 50Hz, 5 Amps |
| Finish | Polyester Powder Coated |
| Cycles | 100% Continuous Duty Rating |
| Dimensions | 1230mm H x 770mm W x 520mm D |
| IP Rating | IP56 |
| Settings | Programmable Configurations, as standard |

Optional Extras

- Pogo Tip End Support
- LED Boom Lights
- Solenoid Lock
- Safety Sensing Edges
- Lorry Height Stop / No Entry Signs
- Bottom Skirt / Hi-Bar (Top & Bottom) Skirting
- Articulated Arm



For more information about our AMS UHD Automatic Barrier, please contact us on:

01254 234248 or sales@automatesystems.co.uk

Unit 7B Petre Court, Petre Road
Clayton le Moors, Lancashire, BB5 5HY
01254 234248 – sales@automatesystems.co.uk

